

12V PSU for Hub 2

A power supply unit, connecting the [Hub 2](#) control panel to a low-voltage power source.

DC input	Input voltage 8–20 V
----------	----------------------

Use the security system with [visual alarm verification](#) in premises lacking electricity or having an unstable power supply. A 12 V power supply unit allows connecting a hub to low-voltage networks or using a backup external battery.

Ajax protects your home, even if it goes on wheels. With a 12 V power supply, the security system can travel with you, connecting to a car or portable battery.

Compatibility

The power supply unit is compatible with Hub 2 central panel. It features a standard socket for connecting the power jack plug and has a bundled terminal adapter.

Installation

12V PSU is installed into the device body, replacing the pre-installed 110/23

Tech Specs

Compatibility	Hub 2
Input voltage	8-20 V DC
Output voltage	4.8 V \pm 3%
Switch-on voltage	8 V \pm 2.5%
Switch-off voltage	6.9-7.5 V (depending on load)
Input current	<1 A
Output current	1,5 A
Connection	Socket: 6,5 x 2 mm Plug: 5,5 x 2,1 mm (power jack)

Dimensions	98 x 70 x 17 mm
Weight	28 g
Complete set	<ol style="list-style-type: none">1. 12V PSU for Hub 22. Terminal adapter3. Quick guide