

SpaceControl

A key fob for controlling security modes. Features a panic button for sending alarms to your inner circle and a security company in case of trouble.

- Authentication to prevent forgery
- Jamming detection and communication channels encryption
- Two-way communication

| | | |
|-------------------------------------|---------------------------------------|--|
| Calls for help in case of emergency | Activates full or partial alarm modes | Indicates command execution with color blink |
|-------------------------------------|---------------------------------------|--|

Principle of operation

The device controls the security modes and sends an alarm signal to the Central Monitoring Station by pressing the buttons on the key fob.

Features

Authentication prevents replacement of the device and false alarms.

Installation and set up

Ready to operate straight out the box: the battery is already installed, therefore there is no need to disassemble the detector. With one click, it can be connected to the hub in the mobile application.

Tech specs

| | |
|----------------------------------|--|
| Classification | Four-button key fob with command delivery indication |
| Compatibility | Operates with all Ajax hubs , and range extenders , ocBridge Plus , uartBridge |
| Number of buttons | 4 |
| False alarm prevention | Yes, long press or double press (firmware version 5.54.1.0 or higher. Manufacture date from March 19, 2020) |
| Deactivation of the panic button | Available |
| Power supply | Battery: CR2032 battery Power supply voltage: 3 V Battery life — up to 5 years |

| | |
|-----------------------------|--|
| Jeweller radio technology | <p>Communication range with central unit — up to 1,300 m in an open space</p> <p>Two-way communication between devices</p> <p>Operating frequencies — 868.0-868.6 MHz</p> <p>Self-adjusting RF output power — up to 20 mW</p> <p>Block encryption based on AES algorithm</p> <p>Device polling period — 12–300 s</p> <p>Learn more about Jeweller ></p> |
| Operating temperature range | -25°C to +50°C |
| Permissible humidity | Up to 95% |
| Dimensions | 65 × 37 × 10 mm |
| Weight | 13 g |
| Certification | Grade 2, CE |
| Warranty | <p>Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.</p> <p>Learn more ></p> |
| Complete set | <p>SpaceControl keyfob</p> <p>CR2032 battery (pre-installed)</p> <p>User's guide</p> |