

23MDPP246

DATATEK 24-PORT CAT6 RACK MOUNTABLE PATCH PANEL

Specifications:

Frame	SPCC
Plastic Housing	ABS
RJ45 Contact Material & Finish	 Nickel-plated phosphor bronze Contact area: 50µ gold-plated
IDC Housing	PC
IDC Terminal Material & Finish	 Tin-plated phosphor bronze Dual tool compatible Suitable for 22-26AWG stranded & solid wire
Insertion Force	900grms for 8 contacts
Retention Strength	7.7kgs between jack & plug
Durability	Jack: 750 cycles plug – jack mating & un-mating test. Insertion cycles/minute max, contact resistance test per 100 cycles. IDC: Max. 200 punching times.
Operating Temperature	-30°C to +68°C

tim

The Datatek 24-Port CAT6 Rack Mountable Patch Panel is of a 1U design meant for installation into 19" Data Cabinets. CAT6 or Category 6 specification supports speeds of up to 10 Gigabit (10GBASE-T).

Features:

(Rear view)

- 24x CAT6 rated RJ45 jacks
- Colour coded labels for T568A & T568B
- CAT6 Performance in Compliance with ANSI/TIA/EIA 568 C.2 Standard
- RCM Compliant
- Colour: Black

Accessories Included:

- Rear cable management rail with cable ties
- 1x set of cage nuts

Product information and pricing up to date as of January 30, 2024 12:11 PM. For more information, visit https://bitek.com.au/