

905

CHANNEL PROCESSING EQUIPMENT 905-PC



Channel processors

**Description**

Channel processor for the UHF and VHF bands, designed to work with adjacent digital and analogue channels. High selectivity and automatic gain control (AGC). Compatible B/G, I, D/K and L standards.

Applications

For use in MATV installations of digital and analogue terrestrial TV where adjacent digital or analogue channels exist with very different levels. By selecting the same input and output channel, the processor works as a filter with AGC, handling the channels independently and eliminating interference. In this way, a perfect equalisation is obtained of all the channels received. By selecting different input and output channels, the processor functions as a programmable digital or analogue channel converter.

Characteristics

Each module consists of an intermediate frequency converter, a double surface acoustic wave filter (SAW) and channel converter. Adjustable frequency for analogue channels in steps of 125KHz. Automatic gain control (AGC) of 40 dB. Permits a feed path to supply power to preamplifiers.

CODE	9050174		
MODEL	PC-526		
Connection	F female		
TV system	AM-TV / DVB-T/T2 / ATSC / ISDB-T / DTMB / DVB-C		
Input frequency range	MHz	44-862	
Output frequency range	MHz	44-862	
Bandwidth	MHz	7/8	
I/O frequency step	MHz	0,125	
I/O offset	MHz	0, $\pm 1/6$, $\pm 1/8$, $2/8$, $\pm 3/8$, $\pm 4/8$	
Input level	dB μ V	45..75 DTT	
		55..85 AM-TV	
Extended input level	dB μ V	40..80 DTT	
		50..90 AM-TV	
Output level	dB μ V	83 \pm 3,0	
Putput level stability	dB	$\pm 0,5$	
Output level adjust	dB	25	
Automatic gain control	dB	>40	
Selectivity	dB	7MHz	< 3 $f_c \pm 3,35$ MHz < 6 $f_c \pm 3,50$ MHz > 30 $f_c \pm 4,00$ MHz > 60 $f_c \pm 4,25$ MHz
		8MHz	< 3 $f_c \pm 3,85$ MHz < 6 $f_c \pm 4,00$ MHz > 30 $f_c \pm 4,45$ MHz > 60 $f_c \pm 4,70$ MHz
Channel flatness	dB	± 1	
Frequency stability	KHz	± 20	
Multiplexing/Diplexing through loss	dB	0,8 \pm 0,2 / 0 \pm 0,2	
Noise figure	dB	6 \pm 0,5	

Spurious in band	dB	<58			
Return loss	dB	>14			
Phase Boise	dBc/Hz	80 @1KHz			
		84 @10KHz			
		99 @100KHz			
Equivalent noise degradation	dB	<1,0			
Output voltage	V	+24			
	mA	60			
Power supply	V	+3.3	+5.2	+12	+24
	mA	350	250	120	0+Preamp.
Operating T close to equipment	°C	-10..+65			
Room T with/without fan	°C	-10..+55/+45			
Protection index		IP 30			
Units per packing		1			
Packing weight	Kg	1.16			
Packing dimensions	mm	265 x 165 x 40			

*Programmable with PS-011 and ASP.