

HILLS. Antenna®



4K
mainstream

H.265
HEVC

HIK

DH

8mp

IP

8HR

PTZ
control

16EWWC

WRIST WORN CCTV TESTER

The 4" IPS touch screen IP Camera Tester is a handy display tool, designed for the maintenance and installation of analog, IP, HD coaxial cameras, as well as other security equipment.

It's 800x480 resolution enables the 16EWWC to display network HD and analog camera feeds in high resolution, whilst offering many ONVIF and analog PTZ control.

Ideal for CCTV installers often need to carry a variety of testing tools to complete their work, this wrist worn, 5-in-1 camera tester makes working conditions safer & increases productivity.

Features:

- Compact wrist-worn design for ease of use
- Supports 8MP TVI, 8MP CVI & 8MP AHD
- CVBS camera testing and PTZ control
- H.265 / H.264, 4K video display via mainstream
- Rapid ONVIF (display & testing), IPC TEST (Non-ONVIF test), HIK test tool (Hikvision camera) & DH test tool (Dahua camera)
- UTP / RJ45 TDR Cable Test – Tests UTP cable connection status
- RJ45 Cable TDR Test – Test cable pair status, length, skew, etc.
- Network Tool – PING test, IP address scan, port flashing, etc.
- Innovative coaxial HD focus, video signal quality test
- IP Discovery – detects all network camera IP addresses
- Media Player Function – Plays 4K video & MKV/MP4 files
- Built-in Wi-Fi – Displays Wi-Fi cameras & creating Wi-Fi hotspot
- 10/100/1000M Ethernet, network state and traffic display
- Self-update software – Install apps with android version

Specifications:

Display	4" touch screen, 800x480 resolution	
Video Mode	CVBS	• 1-Ch BNC input, NTSC/PAL • PTZ & RS485 control, Baud 600-115200bps
	IP Camera Test 4K / H.265 / H.264	• IP Discovery, Quick ONVIF, IPC test, RTSP play, Client APK • Rapid Video (test report) • HIK & Dahua Test Tools
	Coaxial HD Test	• 8MP TVI, CVI & AHD camera tests - 3840x2160p 15 FPS, UTC control/ call OSD menu
Battery Type	Built-in 7.4V 2400mAh Lithium Polymer	
Battery Life	Operating time 8hrs / Charge time 4-5hrs	
Power Output	12V DC 3A & PoE 48V DC (Max. 25.5W)	
Languages	English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc.	
Temperature	-10° to +50° (When in operation)	
Dimensions	126(W) x 83(H) x 33(D) mm	

What's included:

- 1x 4" Tester
- 1x BNC Cable
- 1x Audio Cable
- 1x 12V DC / 1A Adaptor
- 12V DC Power Cable
- Polymer Li-Ion Battery
- 1x Wrist Strap
- 1x RS485 Cable
- 1x UTP Cable Tester
- 1x Carry bag
- 1x Manual

Product information and pricing up to date as of February 24, 2026 2:52 PM. For more information, visit www.hillsantenna.com.au

Brought to you by:



Canberra

1/13 Paspaley Street
Hume, ACT, 2620

02 6260 1874
actsales@bitek.com.au

Sydney

7/463 Victoria Street
Wetherill Park, NSW, 2164

02 9659 2272
orders@bitek.com.au

Melbourne

22 Constance Court
Epping, VIC, 3076

03 9456 9222
melbsales@bitek.com.au

Adelaide

1 Temple Court
Ottoway, SA, 5013

08 8395 4111
sasales@bitek.com.au