

4G LTE Filter with Fly Lead **09ALTEDFL**

FEATURES:

- · Plastic insulated housing
- Connector: 75Ω female F-Type to male Pal with 10cm lead.
 LTE Bandstop filter and GSM filter
 Use in DVB-T TV Antenna & Receiver systems

- · For excellent reception of digital signal



	SPECIFICATIONS	
ТҮРЕ	Bandstop Filter	
DESCRIPTION	Freq. Range (MHz)	Specifications (dB)
INSERTION LOSS	5 - 650	<2
	650 - 682	<3
	682 - 690	<3.5
	690 - 694	<4.2
ATTENUATION	650	>2
	694	>4
	703	>23
	704	>24
	710	>33
	790	>81
	800	>67
	821	>57
	862	>54
RETURN LOSS (dB) IN/OUT	5 - 694	>12
DC POWER PASS	Yes (1A/30V)	
CONNECTION TYPE	F-Type Female (75Ω) to Pal Male	
IMPEDANCE	Input / 75Ω	Output / 75Ω
DIMENSIONS	48 x 28.5 x 19 mm (L x W x H)	
WEIGHT	37g	

PACKAGING	White Box with Label	
WHAT'S INCLUDED	1x Bandstop Filter	
WARRANTY	1 Year	

FOR MORE INFORMATION:

**** 1300 601 915 ✓ orders@bitek.com.au
 ✓ www.bitek.com.au

DISTRIBUTED BY: SITE SITE PTY LTD