



(Colour Box with Label)



16-Way 5-1000MHz F-Type Splitter - 1 Leg Power Pass

10BSPF16

FEATURES:

- Zinc die-cast housing, Tin-plated
- Light weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws Supplied
- · Housing Earth Point and Earth screw supplied
- Screening Factor: 5-1000MHz≥100dB Low insertion loss, high isolation
- Micro-strip circuit design and perfect performance index
- All ports F-Type Female connectors (75Ω)

	FREQUENCY RANGE	INSERTION LOSS	MUTUAL ISOLATION	RETURN LOSS RATIO
SPECIFICATIONS	5-40MHz	≤14.5dB	≥25dB	≥20dB
	40-470MHz	≤14.5dB	≥25dB	≥20dB
	470-860MHz	≤15.5dB	≥25dB	≥18dB
	860-1000MHz	≤16.0dB	≥22dB	≥17dB
SPLITTER TYPE	Free-To-Air (FTA)			
OUTLETS	16			
POWER PASS	Single Port (24V 0.8A MAX.)			
CONNECTION TYPE	F-Type Female (75 Ω)			
MATERIALS	Zinc Die-Cast Housing, Tin-Plated			
INCLUDED ACCESSORIES	Mounting Screws & Earth Screws			
PACKAGING	Colour Box with Label			
WARRANTY	1 Year			

FOR MORE INFORMATION:

1300 601 915 orders@bitek.com.au www.bitek.com.au

DISTRIBUTED BY: SITE SITE PTY LTD