



(11GD510)



(11GD515)



(11GD520)

DIGITEK[®]

Complete Digital Solutions

5-Wire 1-Way TAP

11GD510	10dB
11GD515	15dB
11GD520	20dB

FEATURES:

- Trunk Inputs/Outputs: 4 x Satellite, 1 x Terrestrial
- Tap Outputs: 4 x Satellite, 1 x Terrestrial
- Frequency Range Satellite: 950 - 2150MHz
- Frequency Range Terrestrial: 5 - 862MHz
- Foxtel Approved

SPECIFICATIONS

PRODUCT		11GD510	11GD515	11GD520
DESCRIPTION		10dB 1-Way TAP	15dB 1-Way TAP	20dB 1-Way TAP
FOXTEL APPROVED NUMBER		F30424	F30425	F30541
TRUNK INPUTS/OUTPUTS		4 x SAT, 1 x TERR		
TAP OUTPUTS		4 x SAT, 1 x TERR		
FREQUENCY RANGE	SAT	950-2150MHz		
	TERR	5-862MHz		
TAP LOSS	SAT	7.5-12dB Fixed Slope	12.5-17.5dB Fixed Slope	22-19dB Fixed Slope
	TERR	10dB +/- 2dB	15dB +/- 2dB	20dB +/- 2dB
TRUNK LOSS	SAT	2dB	1dB	1dB
	TERR	1.2dB	1dB	0.5-1dB
DIRECTIVITY	SAT	≥10dB		
	TERR	≥20dB	≥20dB	≥25dB
REJECTION	TERR → SAT	≥13dB	≥18dB	≥22dB
ISOLATION	SAT	≥35dB		
RETURN LOSS	SAT	≥10dB		
	TERR	≥16dB	≥13dB	≥13dB
DC Pass on Sat trunk paths		2A Max		
DC Pass on Sat H tap paths		0.5A Max switchable		
CONNECTOR TYPE		F-Type Female		
DIMENSIONS		182 x 120 x 53 mm		
PACKAGING				
WHAT'S INCLUDED		• 1x 5-Wire 1-Way TAP		
WARRANTY		1 Year		

FOR MORE INFORMATION:

☎ 1300 601 915

✉ orders@bitek.com.au

🌐 www.bitek.com.au

DISTRIBUTED BY: **BITEK PTY LTD**