



(Colour Box with Label)



12-Way 5-1000MHz F-Type Splitter - 1 Leg Power Pass

10BSPF12

FEATURES:

- Zinc die-cast housing, Tin-plated
- Light weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws Supplied
- Housing Earth Point and Earth screw supplied
- Screening Factor: 5-1000MHz \geq 100dB Low insertion loss, high isolation
- Micro-strip circuit design and perfect performance index
- All ports F-Type Female connectors (75 Ω)

	FREQUENCY RANGE	INSERTION LOSS	MUTUAL ISOLATION	RETURN LOSS RATIO
SPECIFICATIONS	5-40MHz	\leq 12.5dB	\geq 25dB	\geq 20dB
	40-470MHz	\leq 12.5dB	\geq 25dB	\geq 20dB
	470-860MHz	\leq 13.5dB	\geq 25dB	\geq 18dB
	860-1000MHz	\leq 14.0dB	\geq 22dB	\geq 17dB
SPLITTER TYPE	Free-To-Air (FTA)			
OUTLETS	12			
POWER PASS	Single Port (24V 0.8A MAX.)			
CONNECTION TYPE	F-Type Female (75 Ω)			
MATERIALS	Zinc Die-Cast Housing, Tin-Plated			
INCLUDED ACCESSORIES	• Mounting Screws & Earth Screws			
PACKAGING	Colour Box with Label			
WARRANTY	1 Year			

FOR MORE INFORMATION:

☎ 1300 601 915 ✉ orders@bitek.com.au 🌐 www.bitek.com.au

DISTRIBUTED BY: **BITEK** BITEK PTY LTD