



2-Way 5-1000MHz F-Type Splitter - 1 Leg Power Pass

10BSPF2

FEATURES:

- Zinc die-cast housing, Tin-plated
- Light weight and compact size

- Easy installation with two edge hole sites
 Mounting Screws Supplied
 Housing Earth Point and Earth screw supplied
 Screening Factor: 5-1000MHz≥100dB
- Micro-strip circuit design and perfect performance index
- All ports F-Type Female connectors (75Ω)

	FREQUENCY RANGE	INSERTION LOSS	MUTUAL ISOLATION	RETURN LOSS RATIO
SPECIFICATIONS	5-40MHz	3.5dB	25dB	20dB
	40-470MHz	3.8dB	28dB	20dB
	470-860MHz	4dB	25dB	18dB
	860-1000MHz	4.3dB	22dB	17dB
SPLITTER TYPE	Free-To-Air (FTA)			
OUTLETS	2			
POWER PASS	Single Port			
CONNECTION TYPE	F-Type Female (75 Ω)			
MATERIALS	Zinc Die-Cast Housing, Tin-Plated			
INCLUDED ACCESSORIES	Mounting Screws & Earth Screws			
PACKAGING	Poly Bag with Label			
WARRANTY	1 Year			
EOD MODE INFORMATION:				

FOR MORE INFORMATION:

DISTRIBUTED BY: SICE PTY LTD