



## 3-Way 5-1000MHz F-Type Splitter - 1 Leg Power Pass

## 10BSPF3

## **FEATURES:**

- · Zinc die-cast housing, Tin-plated
- Light weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws Supplied
- Housing Earth Point and Earth screw supplied
- Screening Factor: 5-1000MHz≥100dB
- Micro-strip circuit design and perfect performance index
- All ports F-Type Female connectors (75Ω)

	FREQUENCY RANGE	INSERTION LOSS	MUTUAL ISOLATION	RETURN LOSS RATIO
SPECIFICATIONS	5-40MHz	5.5dB	25dB	20dB
	40-470MHz	5.8dB	28dB	20dB
	470-860MHz	6dB	25dB	18dB
	860-1000MHz	6.5dB	22dB	17dB
SPLITTER TYPE	Free-To-Air (FTA)			
OUTLETS	3			
POWER PASS	Single Port			
CONNECTION TYPE	F-Type Female (75Ω)			
MATERIALS	Zinc Die-Cast Housing, Tin-Plated			
INCLUDED ACCESSORIES	Mounting Screws & Earth Screws			
PACKAGING	Poly Bag with Label			
WARRANTY	1 Year			

FOR MORE INFORMATION:

DISTRIBUTED BY: SITE SITE PTY LTD