



## 4-Way 5-1000MHz F-Type Splitter - 1 Leg Power Pass

## 10BSPF4

## **FEATURES:**

- Zinc die-cast housing, Tin-platedLight weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws Supplied
- Housing Earth Point and Earth screw supplied
- Screening Factor: 5-1000MHz≥100dB
- Micro-strip circuit design and perfect performance index
- All ports F-Type Female connectors (75Ω)

- All ports 1 - Type I emale e	` '	INCEPTION.		DEE: 1000
	FREQUENCY RANGE	INSERTION LOSS	MUTUAL ISOLATION	RETURN LOSS RATIO
SPECIFICATIONS	5-40MHz	6.8dB	25dB	20dB
	40-470MHz	7.0dB	28dB	20dB
	470-860MHz	7.5dB	25dB	18dB
	860-1000MHz	8.2dB	22dB	17dB
SPLITTER TYPE	Free-To-Air (FTA)			
OUTLETS	4			
POWER PASS	Single Port			
CONNECTION TYPE	F-Type Female (75Ω)			
MATERIALS	Zinc Die-Cast Housing, Tin-Plated			
INCLUDED ACCESSORIES	Mounting Screws & Earth Screws			
PACKAGING	Poly Bag with Label			
WARRANTY	1 Year			
FOR MORE INFORMATION:				

FOR MORE INFORMATION:

\$\ \colon 1300 601 915 \improx orders@bitek.com.au \neq \text{www.bitek.com.au}