



3-Way Passive Splitter

BC15166B

FEATURES:

- Zinc die-cast housing
- Light weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws supplied
 Housing Earth Point and Earth screw supplied
 Screening Factor: 5-2400MHz
- All ports F-Type Female connectors (75Ω)
- Foxtel Approved IPL #G83

SPECIFICATIONS	FREQUENCY RANGE	INSERTION LOSS (MAX.)	ISOLATION (MIN.)	RETURN LOSS IN (MIN.)	RETURN LOSS OUT (MIN.)
	5-40MHz	6.7dB	22dB	17dB	12dB
	40-950MHz	7.5dB	22dB	16dB	15dB
	950-1450MHz	9.3dB	22dB	14dB	14dB
	1450-2150MHz	10.5dB	22dB	17dB	12dB
	2150-2400MHz	11.5dB	22dB	17dB	12dB
SPLITTER TYPE	Free-To-Air (FTA) & Pay TV				
OUTLETS	3				
POWER PASS	All Ports				
CONNECTION TYPE	F-Type Female (75 Ω)				
MATERIALS	Zinc Die-Cast Housing				
INCLUDED ACCESSORIES	Mounting Screws & Earth Screws				
PACKAGING	Display Box				
WARRANTY	1 Year				

FOR MORE INFORMATION: \$\cdot \ 1300 601 915 \rightarrow \ orders@bitek.com.au \ \ \ www.bitek.com.au DISTRIBUTED BY: SICE PTY LTD

