



2-Way Passive Splitter BC15482B

FEATURES:

- Zinc die-cast housing
- Light weight and compact size
- Easy installation with two edge hole sites
- Mounting Screws supplied
- Housing Earth Point and Earth screw supplied
- Screening Factor: 5-2400MHz
- All ports F-Type Female connectors (75Ω)
- Foxtel Approved IPL #F30091

SPECIFICATIONS	FREQUENCY RANGE	INSERTION LOSS (MAX.)	ISOLATION (MIN.)	RETURN LOSS IN (MIN.)	RETURN LOSS OUT (MIN.)
	5-40MHz	3.6dB	18dB	15dB	14dB
	40-950MHz	4.2dB	20dB	15dB	25dB
	950-1450MHz	4.5dB	22dB	17dB	20dB
	1450-2150MHz	5dB	22dB	17dB	18dB
	2150-2400MHz	5.5dB	22dB	15dB	14dB
SPLITTER TYPE	Free-To-Air (FTA) & Pay TV				
OUTLETS	2				
POWER PASS	All Ports				
CONNECTION TYPE	F-Type Female (75Ω)				
MATERIALS	Zinc Die-Cast Housing				
INCLUDED ACCESSORIES	• Mounting Screws & Earth Screws				
PACKAGING	Display Box				
WARRANTY	1 Year				

FOR MORE INFORMATION:

☎ 1300 601 915 ✉ orders@bitek.com.au 🌐 www.bitek.com.au

DISTRIBUTED BY: **BK BITEK PTY LTD**