



2 IN - 8 OUT Multiswitch BC74623H

FEATURES:

- Two satellite inputs and eight outputs for extended distribution
- Earth point attachment for safe installation
- Output ports positioned on one side for neat cable management
- Power pass-through to LNB
- Compatible with both digital and analogue satellite signals
- Reliable F-Type connections
- Foxtel approved – IPL #F30522

APPLICATIONS:

- Satellite TV distribution for homes, apartments, and offices
- Multi-room Foxtel and other satellite systems
- Suitable for digital and analogue signal networks

PACKAGING White Box with Label

WARRANTY 1 Year

FOR MORE INFORMATION:

☎ 1300 601 915 ✉ orders@bitek.com.au 🌐 www.bitek.com.au

DISTRIBUTED BY: **BITEK** BITEK PTY LTD

SPECIFICATIONS

PRODUCT TYPE		Multiswitch			
INPUT PORTS		2 (SATs)			
OUTPUT PORTS		8			
FOXTEL APPROVED		Yes			
FOXTEL IPL		#F30522			
STANDARD		EN50083-3			
ITEM		SPECIFICATION	TYPICAL	Q.C. LIMIT	
FREQUENCY RANGE (SAT)		950-2050MHz			
PORTS	INPUTS	2 (SATs)			
	OUTPUTS	4			
INSERTION GAIN		SAT @950MHz		0dB	0±3B
		SAT @2050MHz		5dB	3±3dB
ISOLATION		SAT Out-Band Rejection		38dB	≥36dB
		Cross Polarization H/V		30dB	≥25dB
		OUT-OUT	SAT	30dB	≥25dB
RETURN LOSS		SAT Input		12dB	≥10dB
		SAT Output		12dB	≥10dB
MAX. INPUT LEVEL		SAT (IMA3 35dB) EN50083-3		94dBµV	≥91dBµV
MIN. OUTPUT LEVEL		SAT (IMA3 35dB) EN50083-3		100dBµV	≥97dBµV
SWITCHING VOLTAGE		Horizontal		16.0 - 19.0 VDC	
		Vertical		11.5 - 14.0 VDC	
LNB POWER SUPPLY		400mA Max.			
POWER CONSUMPTION via STU		60mA Max.			

