




(Top View)



(Bottom View)



(Left-side View)



(Right-side View)

HILLS. Antenna®

16EWWC Wrist Worn CCTV Tester

FEATURES:

- Compact wrist-worn design for ease of use
- 4" touch screen, 800x480 resolutions
- Supports 8MP TVI, 8MP CVI & 8MP AHD
- CVBS camera testing and PTZ control
- H.265 / H.264, 4K video display via mainstream
- Innovative coaxial HD focus, video signal quality test
- Rapid ONVIF – Auto log in, display image, and create testing report
- IPC TEST (Non-ONVIF test), HIK test tool (Hikvision camera) and DH test tool (Dahua camera)
- UTP / RJ45 TDR Cable Test – Tests UTP cable connection status
- Network Tool – PING test, IP address scan, port flashing, etc.
- IP Discovery – press one button to detect all network camera IP addresses
- Rapid Video – press one button to detect all network cameras and auto display
- TesterPlay – Tester, android version mobile phone, PC display all at the same time
- RJ45 Cable TDR Test – Test cable pair status, length, attenuation, reflectivity, impedance, skew, etc.
- Quick drop-down menu for PoE Power, IP Setting, CVBS, LAN Info, etc.
- Self-update software – Install apps with android version
- Media Player Function – Plays 4K video and MKV/MP4 media files
- Built-in Wi-Fi – For displaying Wi-Fi cameras & creating Wi-Fi hotspot
- 10/100/1000M Ethernet, network state and traffic display
- Power Output: 12V DC 3A & PoE 48V DC (Max. power 25.5W)

PACKAGING

Box with Sticker Label

WHAT'S INCLUDED

- 1x 4" Tester
- 1x Wrist Strap
- 1x BNC Cable
- 1x RS485 Cable
- 1x Audio Cable
- 1x UTP Cable Tester
- 1x 12V DC / 1A Adaptor
- 1x Carry bag
- 1x 12V DC Power Cable
- 1x Manual
- 1x Polymer Lithium-Ion Battery (7.4V DC 2400mAh)

WARRANTY

1 Year

FOR MORE INFORMATION:

☎ 1300 601 915 ✉ orders@bitek.com.au 🌐 www.bitek.com.au

DISTRIBUTED BY: **BITEK** BITEK PTY LTD

SPECIFICATIONS

DIPLAY	4" IPS touch screen, 800x480 resolution	
VIDEO MODE	CVBS	1-Ch BNC input, NTSC/PAL
		PTZ control, RS485 control, Baud 600-115200bps
	IP Camera Test 4K / H.265 / H.264	IP Discovery / Quick ONVIF / IPC test / RTSP play / Client APK
CABLE TEST	Coaxial HD Test	Rapid Video (Auto view & testing report)
		HIK Test Tool
		Dahua Test Tool
NETWORK TEST	Zoom Image	8MP TVI camera test - 3840x2160p 12.5/15 FPS, UTC control / call OSD menu
		8MP CVI camera test - 3840x2160p 12.5/15 FPS, UTC control / call OSD menu
		8MP AHD test - 3840x2160p 15 FPS, UTC control / call OSD menu
AUDIO TEST	Zoom, screen snapshot, record, save, view, record and play back	
DATA MONITOR	UTP cable connection status and number	
DROP-DOWN MENU	RJ45 Cable TDR Test (180m max. range)	
LANGUAGE SELECTION	Link monitor, port flashing, Ping test	
POWER OUTPUT	1-Ch audio signal headphone input for sound testing	
BATTERY	Captures and analyzes the command data from controlling device, also can send hexadecimal	
BATTERY LIFE	PoE power switch, IP setting, CVBS, LAN info, etc.	
AUTO OFF	English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc.	
WORKING TEMPERATURE	12V / 3A (temporary power to camera)	
WORKING HUMIDITY	48V PoE (Max. 25.5W)	
DIMENSION / WEIGHT	12V DC / 1A	
	Built-in 7.4V 2400mAh Lithium Polymer battery	
	Normal working time 8hrs / Charge time 4-5hrs	
	1-30 mins	
	-10° to +50°	
	30%-90%	
	126(W) x 83(H) x 33(D) mm / 0.32kg	

